


INDUSTRIAL COMPONENT DATA

RTO 3-TC 3049945 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: RTO 3-TC



Manufacturer	PHOENIX CONTACT
MPN / Reference	RTO 3-TC
Catalog number	3049945
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-9B3FBAC832
Generated	2026-08-01

Product Overview

Feed-through terminal block

Feed-in terminal block with stud connection technology and transparent protective cover, cross-section: 0.1 - 2.5 mm², AWG: 26 - 14, width: 12.3 mm, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Key Commercial Data

Orderkey 3049945

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 377 (C-1-2017)

GTIN 4046356425162

Weight per Piece (excluding packing) 20.890 g

Custom tariff number 85369010

Country of origin CN (China)

General

Note Note: the BE-RT... path extension is to be used for non-insulated cable lugs (see accessories).

Number of levels 1

Number of connections 2
Potentials 1
Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W
Maximum load current 24 A (with a 2.5 mm² conductor cross section)
Nominal current I_N 24 A
Nominal voltage U_N 1000 V
Open side panel Yes
Dimensions
Width 12.3 mm
End cover width 2.2 mm
Length 66 mm
Height NS 35/7,5 51 mm
Height NS 35/15 58.5 mm
Connection data
Note Connection bolts
Connection method Bolt connection
Screw thread M3
Tightening torque, min 0.6 Nm
Tightening torque max 0.8 Nm
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.1 mm²
Conductor cross section flexible max. 2.5 mm²
Min. AWG conductor cross section, flexible 26
Max. AWG conductor cross section, flexible 14
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.1 mm²
Conductor cross section flexible, with ferrule with p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RTO 3-TC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.