


INDUSTRIAL COMPONENT DATA

RTO 3-TC BU 3049835 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: RTO 3-TC BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	RTO 3-TC BU
Catalog number	3049835
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-0FBB2104DD
Generated	2026-08-04

Product Overview

Feed-through terminal block

Feed-through terminal block with stud connection technology and transparent protective cover, cross-section: 0.1 - 2.5 mm², AWG: 26 - 14, width: 12.3 mm, colour: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Key Commercial Data

Orderkey 3049835

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 377 (C-1-2017)

GTIN 4046356425131

Weight per Piece (excluding packing) 20.890 g

Custom tariff number 85369010

Country of origin CN (China)

General

Note Note: the BE-RT... path extension is to be used for non-insulated cable lugs (see accessories).

Number of levels 1

Number of connections 2
Potentials 1
Nominal cross section 2.5 mm²
Color blue
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W
Maximum load current 24 A (with a 2.5 mm² conductor cross section)
Nominal current I_N 24 A
Nominal voltage U_N 1000 V
Open side panel Yes
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2.2 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of tight fit on support Test passed
Tight fit on carrier NS 35
Setpoint 1 N
Result of voltage-drop test Test passed
Requirements, voltage drop ≤ 3.2 mV
Result of temperature-rise test Test passed
Short circuit stability result Test passed
Conductor cross section short circuit testing 2.5 mm²
Short-time current 0.3 kA
Result of thermal test Test passed
Proof of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RTO 3-TC BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.