

INDUSTRIAL COMPONENT DATA

STS 6-TWIN 3038150 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: STS 6-TWIN



Manufacturer	PHOENIX CONTACT
MPN / Reference	STS 6-TWIN
Catalog number	3038150
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-D9B47DF69B
Generated	2026-07-29

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 800 V, nominal current: 41 A, number of connections: 3, connection type: Spring connection, 1st floor, Dimensioning cross-section: 6 mm², cross-section: 0.2 mm² - 10 mm², installation type: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3038150

Packing unit 50 pc

Catalog page Page 185 (C-1-2017)

GTIN 4017918928971

Weight per Piece (excluding packing) 20.320 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 6 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 1.31 W
Maximum load current 57 A (with 10 mm² conductor cross section)
Nominal current I_N 41 A
Nominal voltage U_N 800 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 2.2 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.2 mm² / 0.3 kg
6 mm²/ 1.4 kg
10 mm² / 2 kg
Tensile test result Test passed
Conductor cross section tensile test 0.2 mm²
Tractive force setpoint 10 N
Conductor cross section tensile test 6 mm²
Tractive force setpoint 80 N
Conductor cross section tensile test 10...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / STS 6-TWIN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.