


INDUSTRIAL COMPONENT DATA

UDMTK 5-P/P 3101087 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UDMTK 5-P/P



Manufacturer	PHOENIX CONTACT
MPN / Reference	UDMTK 5-P/P
Catalog number	3101087
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-E702AD00EC
Generated	2026-08-03

Product Overview

Knife disconnect terminal block

Blade interruptible terminal, with threaded sockets for test sockets to accommodate test pins, rated voltage: 400 V, rated current: 10 A, 1st and 2nd floor, connection type: Screw connection, Sizing section: 4 mm², section: 0.2 mm² - 4 mm², 2. Floor, connection type: Screw connection, Sizing section: 4 mm², Section: 0.2 mm² - 4 mm², Mounting: NS 35/7.5, NS 35/15, NS 32, Color: Grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3101087

Packing unit 50 pc

Catalog page Page 479 (C-1-2017)

GTIN 4017918092597

Weight per Piece (excluding packing) 31.720 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of levels 2

Number of connections 4

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V2

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-1

Nominal current I_N 10 A

Maximum load current 10 A (with 4 mm² conductor cross section)

Nominal voltage U_N 400 V

Open side panel No

Dimensions

Width 6.2 mm

Length 93 mm

Height NS 35/7,5 68.5 mm

Height NS 35/15 76 mm

Height NS 32 73.5 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1.5 mm²

2 conductors with same cross section, strande...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UDMTK 5-P/P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.