

INDUSTRIAL COMPONENT DATA

UKK 4-FS 2770561 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UKK 4-FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UKK 4-FS
Catalog number	2770561
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-2EC57A1649
Generated	2026-08-03

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 400 V, nominal current: 20 A, 1. And 2nd floor, connection on the left, connection type: Screw connection, Sizing cross-section: 4 mm², cross-section: 0.2 mm² - 4 mm², connection type: Flat plug connection, mounting: NS 35/7.5, NS 35/15, NS 32, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Enclosures connectivity**

Additional Product Information

Key Commercial Data

Orderkey 2770561

Packing unit 50 pc

Catalog page Page 502 (C-1-2017)

GTIN 4017918067977

Weight per Piece (excluding packing) 14.710 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 6

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V2

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W (the value is multiplied when connecting multiple levels)

Connection method Screw connection

Maximum load current 20 A (with 4 mm² conductor cross section)

Nominal current I_N 20 A

Nominal voltage U_N 400 V

Connection method Slip-on connection

Open side panel Yes

Dimensions

Width 6.2 mm

Length 72 mm

Height NS 35/7,5 59 mm

Height NS 35/15 66.5 mm

Height NS 32 64 mm

End cover width 1.5 mm

Connection data

Connection method Screw connection

Screw thread M3

Tightening torque, min 0.6 Nm

Tightening torque max 0.8 Nm

Stripping length 8 mm

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Min. AWG conductor cross section, flexible 24

Max. AWG conductor cross section, flexible 12

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UKK 4-FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.