


INDUSTRIAL COMPONENT DATA

UT 4/ 1P 3045583 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4/ 1P



Manufacturer	PHOENIX CONTACT
MPN / Reference	UT 4/ 1P
Catalog number	3045583
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-8E581FE8FB
Generated	2026-07-29

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 800 V, nominal current: 32 A, number of connections: 2, connection type: Screw connection / plug-in connection, Sizing cross-section: 4 mm², cross-section: 0.14 mm² - 6 mm², installation class: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3045583

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 345 (C-1-2017)

GTIN 4046356083096

Weight per Piece (excluding packing) 8.460 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W

Maximum load current 32 A (with 6 mm² conductor cross section)

Nominal current I_N 32 A

Nominal voltage U_N 800 V

Open side panel Yes

Insertion/withdrawal cycles mechanical 100

Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending test conductor cross section/weight 0.14 mm² / 0.3 kg

4 mm² / 0.9 kg

6 mm² / 1.4 kg

Tensile test result Test passed

Conductor cross section tensile test 0.14 mm²

Tractive force setpoint 10 N

Conductor cross section tensile test 4 mm²

Tractive force setpoint 60 N

Conductor cross section tensile test 6 mm²

Tractive force setpoint 80 N

Result of tight fit on support Test passed

Tight fit on carrier NS 35

Setpoint 1 N

Short circuit stability result Test passed

Conductor cross section short circuit testing 4 mm²

Short-time current 0.48 kA

Conductor cross....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 4/ 1P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.