

**INDUSTRIAL COMPONENT DATA**

# UT 4-TWIN BU 3044500 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 4-TWIN BU



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | UT 4-TWIN BU                |
| Catalog number  | 3044500                     |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-B05DEC1768               |
| Generated       | 2026-08-04                  |

## Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 500 V, nominal current: 32 A, number of connections: 3, connection type: Screw connection, 1st floor, Dimensioning cross-section: 4 mm<sup>2</sup>, cross-section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting class: NS 35/7.5, NS 35/15, colour: blue

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

## Additional Product Information

Key Commercial Data

Orderkey 3044500

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 229 (C-1-2017)

GTIN 4046356055390

Weight per Piece (excluding packing) 13.740 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 1

Number of connections 3

**Potentials 1**

Nominal cross section 4 mm<sup>2</sup>

Color blue

Insulating material PA

Flammability rating according to UL 94 V0

Area of application Railway industry

Machine building

Plant engineering

Process industry

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 1.02 W

Maximum load current 41 A (In the case of a 6 mm<sup>2</sup> conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors)

Nominal current IN 32 A

Nominal voltage UN 500 V

Open side panel Yes

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) >32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 1...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / UT 4-TWIN BU with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.