

INDUSTRIAL COMPONENT DATA

UTT 2,5-PE 3044665 PHOENIX CONTACT Protective conductor double-level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTTB 2,5-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTT 2,5-PE
Catalog number	3044665
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-A3F75AD4C7
Generated	2026-08-02

Product Overview

Protective conductor double-level terminal block

Double-deck terminal block with protective conductor, number of connections: 4, connection type: Screw connection, cross-section: 0.14 mm² - 4 mm², mounting class: NS 35/7.5, NS 35/15, color: yellow-green

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3044665

Packing unit 50 pc

Catalog page Page 219 (C-1-2017)

GTIN 4017918997038

Weight per Piece (excluding packing) 20.360 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Number of levels 2

Number of connections 4

Nominal cross section 2.5 mm²

Color green-yellow

Insulating material PA
Flammability rating according to UL 94 V0
Area of application Railway industry
Machine building
Plant engineering
Process industry
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-2
Open side panel Yes
Oscillation, broadband noise test result Test passed
Test specification, oscillation, broadband noise DIN EN 50155 (VDE 0115-200):2008-03
Test spectrum Service life test category 1, class B, body mounted
Test frequency f1= 5 Hz to f2= 150 Hz
ASD level 1.857 (m/s²)/Hz
Acceleration 0,8 g
Test duration per axis 5 h
Test directions X-, Y- and Z-axis
Shock test result Test passed
Test specification, shock test DIN EN 50155 (VDE 0115-200):2008-03
Shock form Half-sine
Acceleration 5 g
Shock duration 30 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Relative insulation material temperature index (Elec.; UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTTB 2,5-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.