

**INDUSTRIAL COMPONENT DATA**

# UW 25-POT/S 3073513 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UW 25-POT/S



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | UW 25-POT/S                       |
| Catalog number  | 3073513                           |
| Category        | Panel feed-through terminal block |
| Minimum order   | 25 Pcs                            |
| Document ID     | EO-6DA957075D                     |
| Generated       | 2026-08-03                        |

## Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Terminal connection, number of poles: 1, charging current: 101 A, cross-section: 6 mm<sup>2</sup> - 35 mm<sup>2</sup>, conductor connection direction with respect to the plug direction: 0 °, width: 15.1 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 3073513

Packing unit 25 pc

Catalog page Page 615 (C-1-2013)

GTIN 4046356344685

Weight per Piece (excluding packing) 42.000 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 1

Number of connections 2

Nominal cross section 25 mm<sup>2</sup>

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Maximum load current 125 A

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-1

Nominal current IN 101 A

Maximum load current 125 A

Nominal voltage UN 800 V

Open side panel No

Number of positions 1

Dimensions

Width 15.1 mm

Pitch 15.1 mm

Plate thickness 1 mm ... 6 mm

Connection data

Note Terminal sleeve

Connection side outside

Connection method Screw connection

Note Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.

Conductor cross section solid min. 6 mm<sup>2</sup>

Conductor cross section solid max. 35 mm<sup>2</sup>

Conductor cross section flexible min. 10 mm<sup>2</sup>

Conductor cross section flexible max. 25 mm<sup>2</sup>

Conductor cross section AWG min. 10

Conductor cross section AWG max. 2

Conductor cross section flexible, with ferrule without plastic sleeve min. 4 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 4 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plasti...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UW 25-POT/S with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.