


INDUSTRIAL COMPONENT DATA

VDFK 4/K-DP 0709220 PHOENIX CONTACT Panel feed-through terminal block, Connection method: Screw connection, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: VDFK 4/K-DP



Manufacturer	PHOENIX CONTACT
MPN / Reference	VDFK 4/K-DP
Catalog number	0709220
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-D3DE95FB96
Generated	2026-08-02

Product Overview

Panel feed-through terminal block, Connection method: Screw connection, Solder connection, Load current : 32 A, Cross section: 0.2 mm²

Terminal block, connection type: Screw connection with traction capsule, Weld connection, number of poles: 1, charging current: 32 A, cross-section: 0.2 mm² - 6 mm², AWG 24 - 10, conductor connection direction with respect to the plug direction: 0 °, width: 10 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

General

Rated surge voltage 6 kV

Pollution degree 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-1

Nominal current I_N 32 A

Maximum load current 32 A

Nominal voltage U_N 500 V

Open side panel nein

Number of positions 1

Dimensions

Width 10 mm

Plate thickness 4 mm ... 8 mm

Connection data

Connection side Outside

Connection method Screw connection

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 6 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 4 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 10

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 4 mm²

2 conductors with same cross section, solid min. 0.2 mm²

2 conductors with same cross section, solid max. 1.5 mm²

2 conductors with same cross section, stranded min. 0.2 mm²

2 conductors with same cross section, stranded max. 1.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm²

2 conductors with same cross section, stranded,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VDFK 4/K-DP with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.