

INDUSTRIAL COMPONENT DATA

PT 1,5/S-QUATTRO-MTD 3210328 PHOENIX CONTACT

Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/S-QUATTRO-MTD



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/S-QUATTRO-MTD
Catalog number	3210328
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-48D147AF96
Generated	2026-08-01

Product Overview

Feed-through terminal block

Feed-through terminal, with the same contour as the interruptible terminal, nominal voltage: 400 V, nominal current: 17.5 A, number of connections: 4, connection type: Push-in connection, 1st floor, Dimensioning cross-section: 1.5 mm², cross-section: 0.14 mm² - 1.5 mm², mounting class: NS 35/7.5, NS 35/15, colour: grey

Feed-through terminal block, same shape as disconnect terminal block, nom. voltage: 400 V, nominal current: 17.5 A, number of connections: 4, connection method: Push-in connection, 1 level, Rated cross section: 1.5 mm², cross section: 0.14 mm² - 1.5 mm², mounting type: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Multi-conductor terminal block

Product family PT

Number of connections 4

Number of rows 1

Potentials 1

Data management status

Article revision 01

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Maximum power dissipation for nominal condition 0.56 W

Connection data Number of connections per level 4

Nominal cross section 1.5 mm²

1 level

Stripping length 8 mm ... 10 mm

Internal cylindrical gage A1 / B1

Connection in acc. with standard IEC 60947-7-1

Conductor cross section rigid 0.14 mm² ... 1.5 mm²

Cross section AWG 26 ... 16 (converted acc. to IEC)

Conductor cross section flexible 0.14 mm² ... 1.5 mm²

Conductor cross section, flexible [AWG] 26 ... 16 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.14 mm² ... 1.5 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.14 mm² ... 1 mm² Using the AI-S 1-8 TQ ferrule, Item No. 1200293, is recommended

Nominal current 17.5 A

Maximum load current 17.5 A

Nominal voltage 400 V

Nominal cross section 1.5 mm²

1 level Connection cross sections directly pluggable

Conductor cross section rigid 0.25 mm² ... 1.5 mm²

Conductor cross-section flexible (ferrule without plastic sleeve) 0.34 mm² ... 1.5 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.34 mm² ... 1 mm²

Dimensions Width 3.5 mm

End cover width 0.8 mm

Height 76.9 mm

Depth 30.5 mm

Depth on NS 35/7,5 32 mm

Depth on NS 35/15....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/S-QUATTRO-MTD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.