

INDUSTRIAL COMPONENT DATA

RCK-TGUM/BL16+3/10,0PUR-U 1684069 PHOENIX CONTACT

Master cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: RCK-TGUM/BL16+3/10,0PUR-U



Manufacturer	PHOENIX CONTACT
MPN / Reference	RCK-TGUM/BL16+3/10,0PUR-U
Catalog number	1684069
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-2A323A76E5
Generated	2026-08-04

Product Overview

Master cable

Main cable, application: sensor/actuator box Plastic, number of poles: 19, occupancy of plug-in stations: Double, status indication: No; Main cable connection: M23 plug-in connection, PUR/PVC, cable length: 10 m, shielding: no, Alternative product according to RoHS II without exception 6c (Pb< 0.1%) item code: 1260764

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1684069

Packing unit 1 pc

Catalog page Page 128 (PC-2009)

GTIN 4017918172053

Weight per Piece (excluding packing) 1,900.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

General

Rated voltage 150 V

Number of positions 19

Note The master cable is earmarked for use on the sensor/actuator boxes with an M23 plug-in connection.

Ambient conditions

Degree of protection IP65

IP67

Ambient temperature (operation) -40 °C ... 125 °C (Plug / socket)

Master cable data/connection data

Connection method M23 plug connection

Length of cable 10 m

Insulation material

Housing material PUR

Material of contact, master cable side CU alloy

Material of contact surface, master cable side Gold-plated

Material of the contact carrier on the master cable side PA

Connection assignment

Slot/position = pin = conductor color 1 / 4 (A) = 15 = WH

1 / 2 (B) = 7 = GY/PK

2 / 4 (A) = 5 = GN

2 / 2 (B) = 4 = RD/BU

3 / 4 (A) = 16 = YE

3 / 2 (B) = 8 = WH/GN

4 / 4 (A) = 3 = GY

4 / 2 (B) = 14 = BN/GN

5 / 4 (A) = 17 = PK

5 / 2 (B) = 9 = WH/YE

6 / 4 (A) = 2 = RD

6 / 2 (B) = 13 = YE/BN

7 / 4 (A) = 11 = BK

7 / 2 (B) = 10 = WH/GY

8 / 4 (A) = 1 = VT

8 / 2 (B) = 18 = GY/BN

1-8 / 1 (+ 120 V) = 19 = BN

1-8 / 3 (0 V) = 6 = BU

1-8 / 5 (PE) = 12 = GN/YE

Cable

Cable type PUR/PVC black

Cable type (abbreviation) PUR

Cable abbreviation LiYY11Y-HF

UL AWM style 20549 (80°C/300 V)

Conductor cross section 16x 0.5 mm² (Signal line)

3x 1 mm² (power line)

AWG signal line 20

AWG power supply 17

Cond...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / RCK-TGUM/BL16+3/10,0PUR-U with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.