

INDUSTRIAL COMPONENT DATA

AI-WM 0,75-8 GY 3240543 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: AI-WM 0,75-8 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	AI-WM 0,75-8 GY
Catalog number	3240543
Category	Cable end sleeve
Minimum order	780 Pcs
Document ID	EO-4FE945F1F9
Generated	2026-08-02

Product Overview

Ferrule

Toe cap with insulating letterable collar. The dropouts can be labelled with BLUEMARK when the feeder is used.
Cable lug with sealable insulating collar. Using the magazine it is possible to mark the cable lugs with BLUEMARK.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Ferrules
--------------	----------------------------

Additional Product Information

Key Commercial Data

Orderkey 3240543

Packing unit 780 pc

Minimum order quantity 780 pc

Catalog page Page 209 (C-3-2017)

GTIN 4046356528139

Weight per Piece (excluding packing) 0.230 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length (b) 29 mm

Width (a) 4.6 mm

Sleeve length 8 mm

Inner dimension of the insulating collar (d) 2.9 mm

Ferrule diameter 1.6 mm

Sleeve wall thickness 0.15 mm

Inner diameter (f) 1.3 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Short-term temperature 120 °C

Max. permanent temperature 105 °C (-40°C no load / 0°C dynamic load)

General

Color gray

Components free from silicone and halogen

Flammability rating according to UL 94 HB

Material E-CU

Coating tin-plated (galvanic)

Standards and Regulations

Flammability rating according to UL 94 HB

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027060701eCl@ss 4.127060701eCl@ss 5.027400201eCl@ss 5.127400200eCl@ss 6.027400200eCl@ss
7.027400201eCl@ss 8.027400201eCl@ss 9.027400201

ETIM 3.0EC000005ETIM 4.0EC000005ETIM 5.0EC000005ETIM 6.0EC000005

UNSPSC 6.0130212109UNSPSC 7.090127121703UNSPSC 1127121703UNSPSC 12.0127121703UNSPSC
13.227121703

ETIM for 3240543 Cable terminations and insulation products (EC000005)

Feature Name

Feature Value

Construction type (EF000767)

Standard

Nominal cross section (EF001335)

0.75 mm²

Sleeve length (EF000014)

8....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI-WM 0,75-8 GY with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.