

INDUSTRIAL COMPONENT DATA

A 1,5 -10 3200276 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: A 1,5-10



Manufacturer	PHOENIX CONTACT
MPN / Reference	A 1,5-10
Catalog number	3200276
Category	Cable end sleeve
Minimum order	1000 Pcs
Document ID	EO-5D40762E64
Generated	2026-07-31

Product Overview

Ferrule

Toe cap, length: 10 mm, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Ferrules
--------------	----------------------------

Additional Product Information

Key Commercial Data

Orderkey 3200276

Packing unit 1000 pc

Minimum order quantity 1000 pc

Catalog page Page 480 (C-3-2017)

GTIN 4017918093921

Weight per Piece (excluding packing) 0.080 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length (b) 10 mm

Maximum stripping length 10 mm

Inner dimension of the insulating collar (d) 2.8 mm

Ferrule diameter 1.7 mm

Sleeve wall thickness 0.15 mm

Ambient conditions

Short-term temperature 120 °C

Max. permanent temperature 105 °C

General

Color silver

Material CU-DHP

Coating tin-plated (galvanic)

Conductor category Stranded conductors, class 2, 5, 6 / B, C, K, M

Standards and Regulations

Connection in acc. with standard CSA

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027060701eCl@ss 4.127060701eCl@ss 5.027400201eCl@ss 5.127400200eCl@ss 6.027400200eCl@ss
7.027400290eCl@ss 8.027400201eCl@ss 9.027400201

ETIM 2.0EC000005ETIM 3.0EC000005ETIM 4.0EC000005ETIM 5.0EC000005ETIM 6.0EC000005

UNSPSC 6.0130212109UNSPSC 7.090127121703UNSPSC 1127121703UNSPSC 12.0127121703UNSPSC
13.227121703

ETIM for 3200276 Cable terminations and insulation products (EC000005)

Feature Name

Feature Value

Nominal cross section (EF001335)

1.5 mm²

Sleeve length (EF000014)

10 mm

Insulated (EF000019)

No

Halogen free (EF000025)

Yes

Surface protection (EF000139)

Other

For cables resistant to short circuit (EF001713)

No

With identi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / A 1,5-10 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.