

INDUSTRIAL COMPONENT DATA

A 25 -12 3200357 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: A 25-12



|                 |                  |
|-----------------|------------------|
| Manufacturer    | PHOENIX CONTACT  |
| MPN / Reference | A 25-12          |
| Catalog number  | 3200357          |
| Category        | Cable end sleeve |
| Minimum order   | 100 Pcs          |
| Document ID     | EO-D28113DE6A    |
| Generated       | 2026-07-29       |

Product Overview

Ferrule  
Toe cap, length: 12 mm, colour: silver  
Ferrule, sleeve length: 12 mm, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

|              |                            |
|--------------|----------------------------|
| Catalog path | PHOENIX CONTACT > Ferrules |
|--------------|----------------------------|

Additional Product Information

Technical dataNotesGeneral These ferrules are not included in DIN 46228-1: 1992-08

Product propertiesProduct type Cable end sleeve

Conductor category stranded conductors, class 2, 5, 6 / B, C, K, M

Data management status

Article revision 04

Connection dataConductor connection

Conductor cross section flexible max. 25 mm²

Conductor cross section AWG max. 4

Stripping length 12 mm

DimensionsDimensional drawing

Sleeve length 12 mm

Length contact range 12 mm

Maximum stripping length 12 mm

Ferrule diameter 7.3 mm

Sleeve wall thickness 0.2 mm  
Inner dimensions of the insulating collar 9.5 mm  
Material specificationsColor silver-colored  
Material CU-DHP  
Coating tin-plated (galvanic)  
Surface characteristics Tin-plated  
Mechanical propertiesTechnical data  
Sleeve length 12 mm  
Environmental and real-life conditionsAmbient conditions  
Permanent temperature 105 °C  
Short-term temperature 120 °C  
ETIM for 3200357 Cable terminations and insulation products (EC000005)  
Feature Name  
Feature Value  
Nominal cross section (EF001335)  
25 mm<sup>2</sup>  
Sleeve length (EF000014)  
12 mm  
Insulated (EF000019)  
No  
Halogen free (EF000025)  
No  
Surface protection (EF000139)  
Other  
For cables resistant to short circuit (EF001713)  
No  
With identification flag (EF007954)  
No  
AWG size (EF011789)  
4

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / A 25-12 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.