

INDUSTRIAL COMPONENT DATA

AI 0,25- 6 BU 3203040 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: AI 0,25-6 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	AI 0,25-6 BU
Catalog number	3203040
Category	Cable end sleeve
Minimum order	100 Pcs
Document ID	EO-14C82CEBD1
Generated	2026-07-31

Product Overview

Ferrule
Toe cap, cuff length: 6 mm, length: 10.5 mm, colour: blue
Ferrule, sleeve length: 10.5 mm, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Ferrules
--------------	----------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Cable end sleeve
Data management status
Article revision 02
Connection dataConductor connection
Conductor cross section flexible max. 0.25 mm²
Conductor cross section AWG max. 24
Stripping length 8 mm
DimensionsDimensional drawing
Sleeve length 10.5 mm
Length contact range 6 mm
Maximum stripping length 8 mm
Ferrule diameter 0.8 mm
Sleeve wall thickness 0.15 mm
Insulating collar thickness 0.25 mm

Inner dimensions of the insulating collar 2 mm
Material specificationsColor blue (RAL 5015)
Material CU-DHP
Flammability rating according to UL 94 HB
Coating tin-plated (galvanic)
Surface characteristics Tin-plated
Components free from silicone and halogen
Mechanical propertiesTechnical data
Sleeve length 10.5 mm
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -20 °C ... 105 °C
Permanent temperature 105 °C (-40 °C no load / 0 °C dynamic load)
Short-term temperature 120 °C
Standards and regulationsDesign according to standard Special color
ETIM for 3203040 Cable terminations and insulation products (EC000005)
Feature Name
Feature Value
Construction type (EF000767)
Standard
Nominal cross section (EF001335)
0.25 mm²
Sleeve length (EF000014)
10.5 mm
Insulated (EF000019)
Yes
Material insulation (EF008118)
Other
Halogen free (EF000025)
Yes
Colour (EF000007)
Blue
Surface protection (EF000139)
Other
For cables resistant to short circuit (EF001713)
No
With identification flag (EF007954)
No
AWG size (EF011789...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI 0,25-6 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.