

INDUSTRIAL COMPONENT DATA

AI 10 -18 RD 3200616 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: AI 10-18 RD



|                 |                  |
|-----------------|------------------|
| Manufacturer    | PHOENIX CONTACT  |
| MPN / Reference | AI 10-18 RD      |
| Catalog number  | 3200616          |
| Category        | Cable end sleeve |
| Minimum order   | 100 Pcs          |
| Document ID     | EO-1ADA9D1CE9    |
| Generated       | 2026-07-29       |

Product Overview

Ferrule  
Toe cap, cuff length: 18 mm, length: 28 mm, colour: red  
Ferrule, sleeve length: 28 mm, color: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

|              |                            |
|--------------|----------------------------|
| Catalog path | PHOENIX CONTACT > Ferrules |
|--------------|----------------------------|

Additional Product Information

Technical dataProduct propertiesProduct type Cable end sleeve  
Conductor category stranded conductors, class 2, 5, 6 / B, C, K, M  
Data management status  
Article revision 06  
Connection dataConductor connection  
Conductor cross section flexible max. 10 mm²  
Conductor cross section AWG max. 8  
Stripping length 21 mm  
DimensionsDimensional drawing  
Sleeve length 28 mm  
Length contact range 18 mm  
Maximum stripping length 21 mm  
Ferrule diameter 4.6 mm  
Sleeve wall thickness 0.2 mm

Insulating collar thickness 0.3 mm  
Inner dimensions of the insulating collar 7.5 mm  
Material specificationsColor red (RAL 3001)  
Material CU-DHP  
Flammability rating according to UL 94 HB  
Coating tin-plated (galvanic)  
Surface characteristics Tin-plated  
Components free from silicone and halogen  
Mechanical propertiesTechnical data  
Sleeve length 28 mm  
Environmental and real-life conditionsAmbient conditions  
Permanent temperature 105 °C (-40 °C no load / 0 °C dynamic load)  
Short-term temperature 120 °C  
Standards and regulationsDesign according to standard DIN 46228-4, UL 486F-E  
ETIM for 3200616 Cable terminations and insulation products (EC000005)  
Feature Name  
Feature Value  
Construction type (EF000767)  
Standard  
Nominal cross section (EF001335)  
10 mm<sup>2</sup>  
Sleeve length (EF000014)  
28 mm  
Insulated (EF000019)  
Yes  
Material insulation (EF008118)  
Other  
Halogen free (EF000025)  
Yes  
Colour (EF000007)  
Red  
Surface protection (EF000139)  
Other  
For cables resistant to short circuit (EF001713)  
No  
With identification flag (EF007954)  
No  
AW...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI 10-18 RD with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.