

INDUSTRIAL COMPONENT DATA

AI 1,5 6 BK 3200755 PHOENIX CONTACT Ferrule AI 1,5 6 BK

Brand: PHOENIX CONTACT | Manufacturer Part Number: AI 1,5-6 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	AI 1,5-6 BK
Catalog number	3200755
Category	Cable end sleeve
Minimum order	100 Pcs
Document ID	EO-EE3D034ABC
Generated	2026-07-29

Product Overview

Ferrule AI 1,5 6 BK
Toe cap, cuff length: 6 mm, length: 12 mm, colour: black
Ferrule, sleeve length: 12 mm, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Ferrules
--------------	----------------------------

Additional Product Information

Technical dataNotesGeneral Measurement I2 differs from DIN 46228-4: 1990-09
Product propertiesProduct type Cable end sleeve
Conductor category stranded conductors, class 2, 5, 6 / B, C, K, M
Data management status
Article revision 07
Connection dataConductor connection
Conductor cross section flexible max. 1.5 mm²
Conductor cross section AWG max. 16
Stripping length 9 mm
DimensionsDimensional drawing
Sleeve length 12 mm
Length contact range 6 mm
Maximum stripping length 9 mm
Ferrule diameter 1.7 mm

Sleeve wall thickness 0.15 mm
Insulating collar thickness 0.3 mm
Inner dimensions of the insulating collar 3.4 mm
Material specificationsColor black (RAL 9005)
Material CU-DHP
Flammability rating according to UL 94 HB
Coating tin-plated (galvanic)
Surface characteristics Tin-plated
Components free from silicone and halogen
Mechanical propertiesTechnical data
Sleeve length 12 mm
Environmental and real-life conditionsAmbient conditions
Permanent temperature 105 °C (-40 °C no load / 0 °C dynamic load)
Short-term temperature 120 °C
Standards and regulationsDesign according to standard NFC 63-023

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI 1,5-6 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.