

INDUSTRIAL COMPONENT DATA

AI 16 -12 IV 3201181 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: AI 16-12 IV



Manufacturer	PHOENIX CONTACT
MPN / Reference	AI 16-12 IV
Catalog number	3201181
Category	Cable end sleeve
Minimum order	100 Pcs
Document ID	EO-BC8E490062
Generated	2026-07-31

Product Overview

Ferrule

Toe cap, cuff length: 12 mm, length: 24 mm, colour: ivory

Ferrule, sleeve length: 24 mm, color: ivory

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Ferrules**

Additional Product Information

Technical dataProduct propertiesProduct type Cable end sleeve

Data management status

Article revision 03

Connection dataConductor connection

Conductor cross section flexible max. 16 mm²

Conductor cross section AWG max. 6

Stripping length 16 mm

DimensionsDimensional drawing

Sleeve length 24 mm

Length contact range 12 mm

Maximum stripping length 16 mm

Ferrule diameter 5.8 mm

Sleeve wall thickness 0.2 mm

Insulating collar thickness 0.4 mm

Inner dimensions of the insulating collar 8.8 mm

Material specificationsColor ivory (RAL 1014)

Material CU-DHP

Flammability rating according to UL 94 HB

Coating tin-plated (galvanic)

Surface characteristics Tin-plated

Components free from silicone and halogen

Mechanical propertiesTechnical data

Sleeve length 24 mm

Environmental and real-life conditionsAmbient conditions

Permanent temperature 105 °C (-40 °C no load / 0 °C dynamic load)

Short-term temperature 120 °C

Standards and regulationsDesign according to standard UL 486F-E, NF C 63-023

ETIM for 3201181 Cable terminations and insulation products (EC000005)

Feature Name

Feature Value

Construction type (EF000767)

Standard

Nominal cross section (EF001335)

16 mm²

Sleeve length (EF000014)

24 mm

Insulated (EF000019)

Yes

Material insulation (EF008118)

Other

Halogen free (EF000025)

Yes

Colour (EF000007)

Other

Surface protection (EF000139)

Other

For cables resistant to short circuit (EF001713)

No

With identification flag (EF007954)

No

AWG size (EF011789)

6

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI 16-12 IV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.