

INDUSTRIAL COMPONENT DATA

AI 25 -22 BK 3200739 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: AI 25-22 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	AI 25-22 BK
Catalog number	3200739
Category	Cable end sleeve
Minimum order	50 Pcs
Document ID	EO-63D0710379
Generated	2026-08-02

Product Overview

Ferrule

Toe cap, cuff length: 22 mm, length: 36 mm, colour: black

Ferrule, sleeve length: 36 mm, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Ferrules
--------------	----------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Cable end sleeve

Conductor category stranded conductors, class 2, 5, 6 / B, C, K, M

Data management status

Article revision 06

Connection dataConductor connection

Conductor cross section flexible max. 25 mm²

Conductor cross section AWG max. 4

Stripping length 26 mm

DimensionsDimensional drawing

Sleeve length 36 mm

Length contact range 22 mm

Maximum stripping length 26 mm

Ferrule diameter 7.3 mm

Sleeve wall thickness 0.2 mm

Insulating collar thickness 0.5 mm
Inner dimensions of the insulating collar 11 mm
Material specifications Color black (RAL 9005)
Material CU-DHP
Flammability rating according to UL 94 HB
Coating tin-plated (galvanic)
Surface characteristics Tin-plated
Components free from silicone and halogen
Mechanical properties Technical data
Sleeve length 36 mm
Environmental and real-life conditions Ambient conditions
Permanent temperature 105 °C (-40 °C no load / 0 °C dynamic load)
Short-term temperature 120 °C
Standards and regulations Design according to standard UL 486F-E, NF C 63-023

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI 25-22 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.