

INDUSTRIAL COMPONENT DATA

AI-TWIN 2X 1,5 -12 BK 3200991 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: AI-TWIN 2X 1,5-12 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	AI-TWIN 2X 1,5-12 BK
Catalog number	3200991
Category	Cable end sleeve
Minimum order	100 Pcs
Document ID	EO-CB9488C7B3
Generated	2026-08-04

Product Overview

Ferrule
Toe cap, cuff length: 12 mm, length: 20 mm, colour: black
Ferrule, sleeve length: 20 mm, color: black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Ferrules
--------------	----------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Cable end sleeve
Conductor category stranded conductors, class 2, 5, 6 / B, C, K, M
Data management status
Article revision 06
Connection dataConductor connection
Conductor cross section flexible max. 1.5 mm²
Conductor cross section AWG max. 16
Stripping length 16 mm
DimensionsDimensional drawing
Sleeve length 20 mm
Length contact range 12 mm
Maximum stripping length 16 mm
Ferrule diameter 2.3 mm
Sleeve wall thickness 0.15 mm

Insulating collar thickness 0.3 mm
Inner dimensions of the insulating collar 3.6 mm
Material specificationsColor black (RAL 9005)
Material CU-DHP
Flammability rating according to UL 94 HB
Coating tin-plated (galvanic)
Surface characteristics Tin-plated
Components free from silicone and halogen
Mechanical propertiesTechnical data
Sleeve length 20 mm
Environmental and real-life conditionsAmbient conditions
Permanent temperature 105 °C (-40 °C no load / 0 °C dynamic load)
Short-term temperature 120 °C
Standards and regulationsDesign according to standard DIN 46228-4, UL 486F-F
ETIM for 3200991 Cable terminations and insulation products (EC000005)
Feature Name
Feature Value
Construction type (EF000767)
Twin cable end sleeve
Nominal cross section (EF001335)
1.5 mm²
Sleeve length (EF000014)
20 mm
Insulated (EF000019)
Yes
Material insulation (EF008118)
Other
Halogen free (EF000025)
Yes
Colour (EF000007)
Black
Surface protection (EF000139)
Other
For cables resistant to short circuit (EF001713)
No
With identification....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI-TWIN 2X 1,5-12 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.