

INDUSTRIAL COMPONENT DATA

AI 2,5-8 BU-B 1500 3240667 PHOENIX CONTACT Ferrule

Brand: PHOENIX CONTACT | Manufacturer Part Number: AI 2,5-8 BU-B 1500



Manufacturer	PHOENIX CONTACT
MPN / Reference	AI 2,5-8 BU-B 1500
Catalog number	3240667
Category	Cable end sleeve
Minimum order	1500 Pcs
Document ID	EO-9599447199
Generated	2026-08-03

Product Overview

Ferrule

Conductor dropouts, 2.5 mm², tapered, bushing length: 8 mm, with insulating collar, galvanically tinned, colour: blue, colour range according to DIN 46228-4, CSA certified

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Ferrules

Additional Product Information

Key Commercial Data

Orderkey 3240667

Packing unit 1500 pc

Minimum order quantity 1500 pc

Catalog page Page 487 (C-3-2017)

GTIN 4046356625463

Weight per Piece (excluding packing) 0.170 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length (b) 14 mm

Maximum stripping length 11 mm

Sleeve length 8 mm

Inner dimension of the insulating collar (d) 4.2 mm

Ferrule diameter 2.3 mm

Insulating collar thickness 0.3 mm

Sleeve wall thickness 0.15 mm

Ambient conditions

Short-term temperature 120 °C

Max. permanent temperature 105 °C (-40°C no load / 0°C dynamic load)

General

Color blue

Components free from silicone and halogen

Flammability rating according to UL 94 HB

Material CU-DHP

Coating tin-plated (galvanic)

Conductor category Stranded conductors, class 2, 5, 6 / B, C, K, M

Standards and Regulations

Connection in acc. with standard CSA

Flammability rating according to UL 94 HB

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027060701eCl@ss 4.127060701eCl@ss 5.027400201eCl@ss 5.127400200eCl@ss 6.027400200eCl@ss

7.027400201eCl@ss 8.027400201eCl@ss 9.027400201

ETIM 4.0EC000005ETIM 5.0EC000005ETIM 6.0EC000005

UNSPSC 6.0130212109UNSPSC 7.090127121703UNSPSC 1127121703UNSPSC 12.0127121703UNSPSC

13.227121703

ETIM for 3240667 Cable terminations and insulation products (EC000005)

Feature Name

Feature Value

Construction type (EF000767)

Standard

Nomi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / AI 2,5-8 BU-B 1500 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.