

INDUSTRIAL COMPONENT DATA

FFKDSA/V2-7,62 BU 1068634 PHOENIX CONTACT Terminal for printed circuit board, pitch: 7.62 mm, number of pole..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FFKDSA/V2-7,62 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	FFKDSA/V2-7,62 BU
Catalog number	1068634
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-F14CA4B6D9
Generated	2026-08-06

Product Overview

Terminal for printed circuit board, pitch: 7.62 mm, number of poles: 1, connection type: spring clamp push-in, mounting: Soldering by wave, color: blue

Terminal block for printed circuit board, nominal current: 17.5 A, nominal voltage (III/2): 630 V, nominal cross-section: 1.5 mm², number of rows: 1, number of poles per row: 1, article family: FFKDS(A)/V2, pitch: 7.62 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: blue, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.4 mm, number of welding pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

ETIM for 1068634 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

19.4 mm

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

7.62 mm

Rated current I_n (EF008250)

17.5 A

Rated voltage (EF000228)

630 V

Rated surge voltage (EF002993)

6 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Spring clamp connection

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section multi-wired (EF007343)

1.5 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.3 mm

Length pin (EF006825)

3.4 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Blue

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of PCB fastening (EF008226)

Connecting contact

Type of fastening (EF002442)

Solder

Type of banding (EF007011)

Carton (for SMD)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FFKDSA/V2-7,62 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.