

INDUSTRIAL COMPONENT DATA

FFKDSA1/H-2,54-13 BD:1-13 1716376 PHOENIX CONTACT

Terminal for printed circuit board, nominal current: 6 A, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FFKDSA1/H-2,54-13 BD:1-13



Manufacturer	PHOENIX CONTACT
MPN / Reference	FFKDSA1/H-2,54-13 BD:1-13
Catalog number	1716376
Category	Printed circuit board terminal
Minimum order	10 Pcs
Document ID	EO-62A109CE92
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, nominal current: 6 A, rated voltage: 160 V, pitch: 2.54 mm, number of poles: 13, type of connection: spring clamp push-in, mounting: Soldering by wave, color: green

Terminal block for printed circuit board, nominal current: 6 A, dimensioning voltage (III/2): 160 V, nominal section: 0.5 mm², Number of potentials: 13, Number of rows: 1, Number of poles per row: 13, family of articles: FFKDS(A) 0.5/.. -H, pitch: 2.54 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: green, Pin arrangement: Double linear pin arrangement, Pin length [P]: 3.6 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FFKDSA1/H-2,54-13 BD:1-13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.