


## INDUSTRIAL COMPONENT DATA

# FFKDSA1/H1-5,08- 8 BS:1-8Q 1109679 PHOENIX CONTACT

## Terminal for printed circuit board, pitch: 5,08 mm, numbe..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FFKDSA1/H1-5,08-8 BS:1-8Q



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | PHOENIX CONTACT                |
| MPN / Reference | FFKDSA1/H1-5,08-8 BS:1-8Q      |
| Catalog number  | 1109679                        |
| Category        | Printed circuit board terminal |
| Minimum order   | 1000 Pcs                       |
| Document ID     | EO-2FBA346DAE                  |
| Generated       | 2026-08-04                     |

### Product Overview

Terminal for printed circuit board, pitch: 5,08 mm, number of poles: 8, color: green

Terminal block for printed circuit board, nominal current: 15 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm<sup>2</sup>, number of rows: 1, number of poles per row: 8, article family: FFKDS(A)/H1, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.4 mm, number of solder pins per potential: 2, packaging type: boxed Printed circuit board terminal, nominal current: 15 A, rated voltage (III/2): 400 V, nominal cross section: 1.5 mm<sup>2</sup>, number of rows: 1, number of positions per row: 8, product range: FFKDS(A)/H1, pitch: 5.08 mm, connection method: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.4 mm, number of solder pins per potential: 2, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

### Additional Product Information

Technical dataProduct propertiesProduct type Printed circuit board terminal

Product family FFKDS(A)/H1

Product line COMBICON Terminals S

Number of positions 8

Pitch 5.08 mm

Number of rows 1

Pin layout Linear pinning

Solder pins per potential 2  
Data management status  
Article revision 00  
Electrical propertiesNominal current IN 15 A  
Nominal voltage UN 400 V  
Rated voltage (III/3) 250 V  
Rated surge voltage (III/3) 4 kV  
Rated voltage (III/2) 400 V  
Rated surge voltage (III/2) 4 kV  
Rated voltage (II/2) 630 V  
Rated surge voltage (II/2) 4 kV  
Connection dataConnection technology  
Type PC terminal block can be aligned  
Nominal cross section 1.5 mm<sup>2</sup>  
Conductor connection  
Connection method Push-in spring connection  
Conductor cross section rigid 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section flexible 0.2 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section AWG 24 ... 16  
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>  
Stripping length 10 mm  
MountingMounting type Wave soldering  
Pin layout Linear pinning  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201  
Contact material Cu alloy  
Surface characteristics Tin-plated  
Metal surface terminal point (top layer) Tin (5 - 7 µm Sn)  
Metal surface terminal point (middle layer) Nickel (2 - 3 µm Ni)  
Metal surface soldering area (top layer) Tin (5 - 7 µm Sn)  
Metal...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FFKDSA1/H1-5,08-8 BS:1-8Q with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.