

INDUSTRIAL COMPONENT DATA

FFKDSA1/H2-5,08- 3 BD:+,- 1813024 PHOENIX CONTACT PCB terminal, rated current: 15 A, rated voltage (III/2): ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FFKDSA1/H2-5,08- 3 BD:+,-



Manufacturer	PHOENIX CONTACT
MPN / Reference	FFKDSA1/H2-5,08- 3 BD:+,-
Catalog number	1813024
Category	Printed circuit board terminal
Minimum order	1000 Pcs
Document ID	EO-7C71EA3F6B
Generated	2026-08-05

Product Overview

PCB terminal, rated current: 15 A, rated voltage (III/2): 400 V, rated cross-section: 1.5 mm², number of rows: 1, number of poles per row: 3, item family: FFKDS(A)/H2, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Wave soldering, driver/printed circuit board connection direction: 0°, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 2, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FFKDSA1/H2-5,08- 3 BD:+,- with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.