

INDUSTRIAL COMPONENT DATA

FFKDSA1/V1-5,08-22 BU 1715991 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 320 V, pitch: 5,08 mm

Brand: PHOENIX CONTACT | Manufacturer Part Number: FFKDSA1/V1-5,08-22 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	FFKDSA1/V1-5,08-22 BU
Catalog number	1715991
Category	Printed circuit board terminal
Minimum order	25 Pcs
Document ID	EO-C077DEFAF9
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, rated voltage: 320 V, pitch: 5,08 mm, number of poles: 22, assembly: Soldering by wave, color: blue

Terminal block for printed circuit board, nominal current: 15 A, dimensioning voltage (III/2): 400 V, nominal cross-section: 1.5 mm², Number of potentials: 22, Number of rows: 1, Number of poles per row: 22, article family: FFKDS(A)/V1, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90°, color: blue, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.4 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Terminal for printed circuit board, nominal current: 15 A, rated voltage: 320 V, pitch: 5,08 mm, number of poles: 22, type of connection: spring clamp push-in, mounting: Soldering by wave direction for connection conductor/pcb: 90°, color: blue
Data commercial

Key order One million seven hundred fifteen thousand nine hundred ninety one

Packing unit 25 pcs

Key selling AAABFA -

Minimum order quantity 25 pcs

EAN Four trillion fifty five billion six hundred twenty six million four hundred forty nine thousand four hundred twenty five

Unit weight (excluding packaging) 23,352 g

Tariff number tariff Eighty five million three hundred sixty nine thousand ten

Dimensions

Length [l] 12.7 mm

Step 5,08 mm

Average 106,68 mm

Width [w] 114,26 mm

Height of construction 13,6 mm

Height [h] 17 mm

Length of pin [P] 3.4 mm

Separation between rods 7.62 mm

Diameter hole 1.3 mm

Overview

Family of articles FFKDS(A)/V1

Nominal cross section 1.5 mm²

Surface pin welding

Number of poles Twenty two

Environmental Product Compliance

China RoHS Space of time for the intended use: unlimited = FEUP-e

No dangerous substances above the thresholds

Ratings

eCl@ss

eCl@ss 5.1 Twenty seven million two hundred sixty one thousand one hundred

eCl@ss 6.0 Twenty seven million two hundred sixty one thousand one hundred

eCl@ss 7.0 Twenty seven million four hundred forty thousand four hundred one

eCl@ss 8.0 Twenty seven million four hundred forty thousand four hundred one

eCl@ss 9.0 Twenty seven million four hundred for...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FFKDSA1/V1-5,08-22 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.