

INDUSTRIAL COMPONENT DATA

FFKDSA1/V1-5,08- 4 BD:X4 1005459 PHOENIX CONTACT

Terminal for printed circuit board, rated voltage: 320 V, p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FFKDSA1/V1-5,08- 4 BD:X4



Manufacturer	PHOENIX CONTACT
MPN / Reference	FFKDSA1/V1-5,08- 4 BD:X4
Catalog number	1005459
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-9E79B81515
Generated	2026-08-05

Product Overview

Terminal for printed circuit board, rated voltage: 320 V, pitch: 5,08 mm, number of poles: 4, type of connection: spring clamp push-in, mounting: Soldering by wave, color: green

Terminal block for printed circuit board, nominal current: 15 A, dimensioning voltage (III/2): 400 V, nominal cross-section: 1.5 mm², Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, article family: FFKDS(A)/V1, pitch: 5.08 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.4 mm, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FFKDSA1/V1-5,08- 4 BD:X4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.