

INDUSTRIAL COMPONENT DATA

FK-MC 0,5/ 6-ST-2,5 AU BD:1-6 1707335 PHOENIX CONTACT

Plug-in part, rated current: 4 A, number of poles: 6, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MC 0,5/ 6-ST-2,5 AU BD:1-6



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MC 0,5/ 6-ST-2,5 AU BD:1-6
Catalog number	1707335
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-7BAF64C314
Generated	2026-08-06

Product Overview

Plug-in part, rated current: 4 A, number of poles: 6, pitch: 2.5 mm, connection type: Push-in spring connection, color: green, contact surface: Gold

Connector for printed circuit board, nominal section: 0.5 mm², color: green, nominal current: 4 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Female, number of potentials: 6, number of rows: 1, number of poles: 6, number of connections: 6, family of articles: FK-MC 0.5/.. -ST, pitch: 2.5mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON FK-MC 0.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Plug component, nominal current: 4 A, number of positions: 6, pitch: 2.5 mm, connection method: Push-in spring connection, color: green, contact surface: Gold

Your advantages

Gold-plated contacts ensure transfer quality remains stable over the long termTime saving push-in connection, tools not requiredDefined contact force ensures that contact remains stable over the long termIntuitive use through colour coded actuation leverOperation and conductor connection from one direction enable integration into front of deviceQuick and convenient testing using integrated test optionKey Commercial Data

Orderkey 1707335

Packing unit 1

GTIN 4046356917674

Custom tariff number 85366990

General

Range of articles FK-MC 0,5/..-ST

Type of contact Female connector

Number of positions 6

Connection method Push-in spring connection

Rated voltage (III/3) 100 V

Connection in acc. with standard EN-VDE

Nominal current IN 4 A

Nominal cross section 0.5 mm²

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 0.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 0.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 0.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 20

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MC 0,5/ 6-ST-2,5 AU BD:1-6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.