

INDUSTRIAL COMPONENT DATA

DEK-REL- 24/1/SEN/SO123 2964940 PHOENIX CONTACT

Relay terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: DEK-REL-24/1/SEN/SO123



Manufacturer	PHOENIX CONTACT
MPN / Reference	DEK-REL-24/1/SEN/SO123
Catalog number	2964940
Category	Switching relay
Minimum order	10 Pcs
Document ID	EO-5FF799A714
Generated	2026-08-05

Product Overview

Relay terminal block

Borne-sensor relay, with soldered miniature relays, contact (AgNi+Au): Small to medium powers, 1 open contact, input voltage 24 V AC/DC, for mounting on NS 35/7.5, terminal width 6.2 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Relays**

Additional Product Information

Key Commercial Data

Orderkey 2964940

Packing unit 10 pc

GTIN 4017918415686

Weight per Piece (excluding packing) 24.920 g

Custom tariff number 85364900

Country of origin CN (China)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.027371601eCl@ss 5.127371600eCl@ss 6.027371600eCl@ss 7.027371601eCl@ss 8.027371601eCl@ss
9.027371601

ETIM 2.0EC001437ETIM 3.0EC001437ETIM 4.0EC001437ETIM 5.0EC001437ETIM 6.0EC001437

UNSPSC 6.0130211916UNSPSC 7.090139121515UNSPSC 1139121515UNSPSC 12.0139121515UNSPSC
13.239122334

ETIM for 2964940 Relays (EC001437)

Feature Name

Feature Value

Type of electric connection (EF003961)

Screw connection

Complete with socket (EF003359)

No

With detachable clamps (EF003340)

No

With LED indication (EF005950)

No

Rated control supply voltage AC 50 Hz (EF003978)

19.2 V

Rated control supply voltage AC 60 Hz (EF003979)

19.2 V

Rated control supply voltage DC (EF003980)

19.2 V

Voltage type for actuating (EF008242)

AC/DC

Number of contacts as normally closed contact (EF008255)

0

Number of contacts as normally open contact (EF008256)

0

Number of contacts as change-over contact (EF008257)

0

With forced-guided contacts (EF003357)

No

Width (EF000008)

6.2 mm

Height (EF000040)

80 mm

Depth (EF000049)

56 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DEK-REL-24/1/SEN/SO123 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.