

INDUSTRIAL COMPONENT DATA

SAC-8P-30,0-PUR/M12FS VA 1401260 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-8P-30,0-PUR/M12FS VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-8P-30,0-PUR/M12FS VA
Catalog number	1401260
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-98498161CF
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, free cable end, to straight connection female M12, cable length: 30 m

Sensor/actuator cable, 8-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, cable length: 30 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 8

Electrical propertiesNominal voltage UN 30 V AC

30 V DC

Mechanical propertiesMechanical data

Insertion/withdrawal cycles >= 100

ConnectorConnection 1

Type free cable end

Connection 2

Type Socket straight M12

Number of positions 8

Cable/line Cable length 30 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 46 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 8
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 32x 0.10 mm
AWG signal line 24
Conductor cross section 8x 0.25 mm² (Signal line)
Wire diameter incl. insulation 1.17 mm ±0.02 mm
External cable diameter 5.90 mm ±0.15 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material, filler PE
Material wire insulation PP
Single wire, color white, brown, green, yellow, gray, pink, blue, red
Thickness, insulation ≥ 0.21 mm
Thickness, outer sheath approx. 0.80 mm
Overall twist 8 wires around filler to the core
Max. conductor resistance ≤ 78 Ω/km
Insulation resistance ≥ 1 GΩ*km
Wave impedance 100 Ω ±15 % (with 1 MHz)
Cable capacity ≤ 70 pF/m
Nominal voltage, cable ≤ 300 V
Test voltage ≥ 3000 V
Minimum bending radius, fixed installation 8 x D
Minimum bending radius, flexible installation 10 x D
Smallest bending radius, fixed installation 48 mm
Smallest bending radius, movable installation 59 mm
Dynamic load capacity (bending...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-8P-30,0-PUR/M12FS VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.