

INDUSTRIAL COMPONENT DATA

MSTBC 2,5/16-STZF-5,08 GY 1712824 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTBC 2,5/16-STZF-5,08 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	MSTBC 2,5/16-STZF-5,08 GY
Catalog number	1712824
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-450B9E9CD7
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact type: Female, number of potentials: 16, number of rows: 1, number of poles: 16, number of connections: 16, family of articles: MSTBC 2.5/.. -STZF, pitch: 5.08 mm, connection type: Crimped connection, conductor/printed circuit board connection direction: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON MSTB 2.5, locking: Screw locking, fixing type: Air clamping (screw), packaging type: boxed packed, Corresponding crimped female contacts, with indications regarding the current [A] and the range of conductor cross-sections [mm²]: 10A/MSTBC-MT 0.5-1.0 (3190564); 10A/MSTBC-MT 0.5-1.0 BA (3190645); 12A/MSTBC-MT 1.5-2.5 (3190551); 12A/MSTBC-MT 1.5-2.5 BA (3190658). BA = Contacts on Ribbon

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1712824

Packing unit 1

GTIN 4055626300351

Custom tariff number 85472000

Dimensions

Width [w] 19.82 mm

Pitch 5.08 mm

Dimension a 76.2 mm

General

Range of articles MSTBC 2,5/..-STZF

Number of positions 16

Connection method Crimp connection

Insulating material group I

Rated voltage (III/2) 320 V

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Flammability rating according to UL 94 V0

Screw thread

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 5.0EC002638ETIM 6.0EC002638

ETIM for 1712824 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of poles (EF001391)

16

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5.08 mm

Modular spacing connections (EF006827)

5.08 mm

Angle contact/conductor connection (EF007546)

Other

Rated current In (EF008250)

12 A

Rated voltage (EF000228)

320 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.5 mm²

Type of electric connection (EF003961)

Crimp connection

Connectable cable type (EF006816)

Tubular cable....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTBC 2,5/16-STZF-5,08 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.