

INDUSTRIAL COMPONENT DATA

FK-MCP 1,5/ 4-ST-3,5 BD:1-4 1724815 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MCP 1,5/ 4-ST-3,5 BD:1-4



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MCP 1,5/ 4-ST-3,5 BD:1-4
Catalog number	1724815
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-E24A15829A
Generated	2026-08-04

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: FK-MCP 1.5/.. -ST, pitch: 3.5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1724815

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4046356127332

Weight per Piece (excluding packing) 3.430 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 21 mm

Width [w] 14.9 mm

Height [h] 12.4 mm

Pitch 3.5 mm

Dimension a 10.5 mm

General

Range of articles FK-MCP 1,5/..-ST

Number of positions 4

Connection method Push-in spring connection

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 16

Minimum AWG according to UL/CUL 28

Maximum AWG according to UL/CUL 16

Specifications for ferrules

Recommended crimping pliers 1212034 CRIMPFOX 6

Ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm²; Length: 7 mm ... 9 mm

Cross section: 0.34 mm²; Length: 7 mm ... 9 mm

Cross section: 0.5 mm²; Length: 8 mm ... 9 mm

Cross section...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MCP 1,5/ 4-ST-3,5 BD:1-4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.