


INDUSTRIAL COMPONENT DATA

FK-MCP 1,5/ 5-ST-3,81GY35BD-D0 1105116 PHOENIX CONTACT Connector for printed circuit board, nominal current:..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MCP 1,5/ 5-ST-3,81GY35BD-D0



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MCP 1,5/ 5-ST-3,81GY35BD-D0
Catalog number	1105116
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-59391AD607
Generated	2026-08-03

Product Overview

Connector for printed circuit board, nominal current: 8 A, number of poles: 5, pitch: 3,81 mm, type of connection: spring clamp push-in, color: light grey, surface contacts: Tin

Connector for printed circuit board, nominal section: 1.5 mm², color: bright gray, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of rows: 1, number of poles: 5, family of articles: FK-MCP 1.5/..-ST, pitch: 3.81 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross-section: 1.5 mm², colour: light grey, rated current: 8 A, dimensioning voltage (III/2): 160 V, contact surface: Sn, contact connection type: Female, number of rows: 1, number of poles: 5, product series: FK-MCP 1.5/..-ST, pitch: 3.81 mm, connection type: Push-in spring connection, conductor/board connection direction: 0°, plug system: COMBICON MC 1.5, locking: none, fastening type: none, packaging type: packed in carton

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataArticle featuresProduct Type Printed circuit board connector

Product Family FK-MCP 1.5/..-ST

Product Line COMBICON Connectors S

Number of poles 5

Step 3.81 mm
Number of rows 1
Data maintenance status
Article review 00
Electrical characteristics Rated Current IN 8 A
Rated voltage UN 160 V
Mass Resistivity 1.4 m?
Sizing voltage (III/3) 160 V
Sizing impulse voltage (III/3) 2.5 kV
Sizing voltage (III/2) 160 V
Sizing Impulse Voltage (III/2) 2.5 kV
Sizing voltage (II/2) 320 V
Sizing Impulse Voltage (II/2) 2.5 kV
Connection data Connection technology
type Standard
Connector system COMBICON MC 1.5
Nominal cross-section 1.5 mm²
Contact Connection Type female
Blockage
Clamping Type absent
Fixing flange absent
Conductor connection
Link Push-in spring connection
Conductor/board connection direction 0 °
Rigid conductor cross-section 0.14 mm² ... 1.5 mm²
Flexible conductor cross-section 0.14 mm² ... 1.5 mm²
Conductor cross-section AWG 26 ... 16
Flexible conductor cross-section with cable lug without plastic collar 0.25 mm² ... 1.5 mm²
Flexible conductor cross-section with mounted lug and plastic collar 0.25 mm² ... 0.75 mm²
Buffer Gauge a x b / diameter 2.4 mm x 1.5 mm / -
Length of the section to be stripped 9 mm
Indications for ferrules without isolation collar
Recommended crimping tool 1212034 CRIMPFOX 6
cable lug without insulating collar, in accordance with DIN 46228-1 Cross-section: 0.25 mm²; Length: 7 mm
Cross-section: 0.34 mm²; Length: 7 mm
Cross-section: 0.5 mm²; Len...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MCP 1,5/ 5-ST-3,81GY35BD-D0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.