


INDUSTRIAL COMPONENT DATA

FK-MCP 1,5/ 5-STF-3,5BD11-GNDQ 1107051 PHOENIX CONTACT Connector for printed circuit board, number of poles:...

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MCP 1,5/ 5-STF-3,5BD11-GNDQ



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MCP 1,5/ 5-STF-3,5BD11-GNDQ
Catalog number	1107051
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-050E8BC527
Generated	2026-08-06

Product Overview

Connector for printed circuit board, number of poles: 5, pitch: 3.5 mm, color: green

Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of rows: 1, number of poles: 5, family of articles: FK-MCP 1.5/.. -STF, pitch: 3.5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: Screw lock, fixing type: Air clamping (screw), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataItem PropertiesProduct Type Printed Circuit Board Connector

Product Family FK-MCP 1.5/.. -STF

Product Line COMBICON Connectors S

Number of poles 5

Step 3.5 mm

Number of rows 1

Data Maintenance Status

Article Review 00

Electrical PropertiesNominal Current IN 8 A

Nominal voltage UN 160 V
Contact resistance 2 mΩ
Sizing voltage (III/3) 160 V
Dimensioning transient voltage (III/3) 2.5 kV
Dimensioning voltage (III/2) 160 V
Dimensioning Transient Voltage (III/2) 2.5 kV
Nominal voltage (II/2) 320 V
Dimensioning transient voltage (II/2) 2.5 kV
Connection dataConnection technology
Construction Standard
Connector System COMBICON MC 1.5
Nominal Section 1.5 mm²
Contact Connection Type Female
Blockade
Locking system Screw lock
Clamping flange Overhead clamping (screw)
Tightening torque 0.3 Nm
Connecting Conductors
Connection type Push-in spring connection
Connection Direction Driver/PCB 0 °
Rigid conductor section 0.14 mm² ... 1.5 mm²
Flexible conductor section 0.14 mm² ... 1.5 mm²
AWG Conductor Section 26 ... 16
Flexible conductor section with toe cap, without plastic sleeve 0.25 mm² ... 1.5 mm²
Flexible conductor section with toe cap, with plastic sleeve 0.25 mm² ... 0.5 mm²
Male gauge a x b / Diameter 2.4 mm x 1.5 mm / -
Peel Length 9 mm
Facts about toe caps without an insulated collar
Recommended crimp pliers 1212034 CRIMPFOX 6
toe caps without insulating collar, according to DIN 46228-1 Cross-section: 0.25 mm²; Length: 7 mm
Cross-section: 0.34 mm²; Length: 7 mm
Cross-se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MCP 1,5/ 5-STF-3,5BD11-GNDQ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.