


INDUSTRIAL COMPONENT DATA

FK-MPT 0,5/ 2-ICVA-3,5 R24 1701301 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MPT 0,5/ 2-ICVA-3,5 R24



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MPT 0,5/ 2-ICVA-3,5 R24
Catalog number	1701301
Category	Printed circuit board connector
Minimum order	300 Pcs
Document ID	EO-6756FB1B83
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 0.5 mm², color: green, nominal current: 3 A, dimensioning voltage (III/2): 250 V, contact surface: Tin, contact type: Female connection, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: FK-MPT 0.5/.. -ICVA, pitch: 3.5 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 3.3 mm, number of welding pins per potential: 1, plug-in system: COMBICON COMPACT FK-MPT - IC, Plug-in face orientation: Standard, Lock: without, fixing type: without, packaging type: 24 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1701301

Packing unit 1

GTIN 4046356525343

Custom tariff number 85366930

Dimensions

Length [L] 9.1 mm

Width 9.5 mm

Pitch 3.5 mm

Dimension a 3.5 mm

Width [w] 9.5 mm

Height [h] 12.1 mm

Height 8.8 mm

Length of the solder pin 3.3 mm

Pin dimensions 0.3 x 0.9 mm

Length 9.1 mm

General

Range of articles FK-MPT 0,5/..-ICVA

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 3 A

Color green

Number of positions 2

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MPT 0,5/ 2-ICVA-3,5 R24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.