


INDUSTRIAL COMPONENT DATA

FK-MPT 0,5/ 5-3,5 GY LCBK 1742004 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MPT 0,5/ 5-3,5 GY LCBK



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MPT 0,5/ 5-3,5 GY LCBK
Catalog number	1742004
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-8AB0F67E7C
Generated	2026-08-03

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 4 A, dimensioning voltage (III/2): 250 V, nominal section: 0.5 mm², number of potentials: 5, number of rows: 1, number of poles per row: 5, family of articles: FK-MPT 0.5/.. -V, pitch: 3.5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 90 °, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1742004

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356294973

Weight per Piece (excluding packing) 1.710 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Length [l] 7 mm

Pitch 3.5 mm

Dimension a 14 mm

Width [w] 18 mm

Height 9.5 mm

Height [h] 13 mm

Solder pin [P] 3.5 mm

Pin spacing 3.5 mm

Hole diameter 1 mm

General

Range of articles FK-MPT 0,5/..-V

Rated surge voltage (III/3) 2.5 kV

Rated surge voltage (III/2) 2.5 kV

Rated surge voltage (II/2) 2.5 kV

Rated voltage (III/3) 160 V

Rated voltage (III/2) 250 V

Rated voltage (II/2) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 4 A

Nominal cross section 0.5 mm²

Solder pin surface

Stripping length 6.5 mm

Number of positions 5

Connection data

Conductor cross section AWG min. 26

Conductor cross section AWG max. 20

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027141109eCl@ss 4.127141109eCl@ss 5.027141190eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss
7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 6.0130211801UNSPSC 7.090139121432UNSPSC 1139121432UNSPSC 12.0139121432UNSPSC
13.239121432

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MPT 0,5/ 5-3,5 GY LCBK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.