


INDUSTRIAL COMPONENT DATA

FK-MPT 0,5/ 7-ICVA-3,5 GN 1724158 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MPT 0,5/ 7-ICVA-3,5 GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MPT 0,5/ 7-ICVA-3,5 GN
Catalog number	1724158
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-3B89E3CABF
Generated	2026-08-06

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 0.5 mm², color: green, nominal current: 3 A, dimensioning voltage (III/2): 250 V, contact surface: Tin, contact type: Female connection, Number of potentials: 7, Number of rows: 1, Number of poles per row: 7, number of connections: 7, family of articles: FK-MPT 0.5/.. -ICVA, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 3.3 mm, Stecksystem: COMBICON COMPACT FK-MPT - IC, Lock: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1724158

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356123952

Weight per Piece (excluding packing) 1.290 g

Custom tariff number 85366930

Country of origin DE (Germany)

Dimensions

Length [l] 9.1 mm

Width 27 mm

Pitch 3.5 mm

Dimension a 21 mm

Width [w] 27 mm

Height [h] 12.1 mm

Height 8.8 mm

Length of the solder pin 3.3 mm

Pin dimensions 0.3 x 0.9 mm

Length 9.1 mm

General

Range of articles FK-MPT 0,5/...-ICVA

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 3 A

Color green

Number of positions 7

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MPT 0,5/ 7-ICVA-3,5 GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.