

INDUSTRIAL COMPONENT DATA

FK-MPT 0,5/ 8-ST-3,5 (VPE1000) 1932041 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FK-MPT 0,5/ 8-ST-3,5 (VPE1000)



Manufacturer	PHOENIX CONTACT
MPN / Reference	FK-MPT 0,5/ 8-ST-3,5 (VPE1000)
Catalog number	1932041
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-59E29E52CB
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 0.5 mm², color: green, nominal current: 4 A, nominal voltage (III/2): 250 V, contact surface: Tin, contact type: Female, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 16, family of articles: FK-MPT 0.5/.. -ST, pitch: 3.5mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, pin arrangement: Linear pin arrangement, plug-in system: COMBICON PST 1.0, lock: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross section: 0.5 mm², color: green, nominal current: 4 A, rated voltage (III/2): 250 V, contact surface: Sn, contact connection type: Socket, number of potentials: 8, number of rows: 1, number of positions: 8, number of connections: 16, product range: FK-MPT 0.5/.. -ST, pitch: 3.5 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0°, pin layout: Linear pinning, plug-in system: COMBICON PST 1,0, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1932041

Packing unit 1000 pc

Minimum order quantity 1000 pc

Note Made to Order (non-returnable)

GTIN 4017918853044

Weight per Piece (excluding packing) 2.720 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 9.5 mm

Width [w] 28.5 mm

Height [h] 8.5 mm

Pitch 3.5 mm

Dimension a 24.5 mm

General

Range of articles FK-MPT 0,5/..-ST

Number of positions 8

Connection method Push-in spring connection

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 4 A

Nominal cross section 0.5 mm²

Connection data

Conductor cross section solid min. 0.12 mm²

Conductor cross section solid max. 0.5 mm²

Conductor cross section AWG min. 26

Conductor cross section AWG max. 20

Minimum AWG according to UL/CUL 28

Maximum AWG according to UL/CUL 20

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss
7.027440309eCl@ss 8.027440309eCl@ss 9.027440309

ETIM 3.0EC001121ETIM 4.0EC002643ETIM 5.0EC002638ETIM 6.0EC002638

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC
13.239121409

ETIM for 1932041 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FK-MPT 0,5/ 8-ST-3,5 (VPE1000) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.