

INDUSTRIAL COMPONENT DATA

FKC 2,5/10-ST-5,08 BD:10-1SO 1367611 PHOENIX CONTACT

Printed circuit board connector, nominal section: 2.5 m..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKC 2,5/10-ST-5,08 BD:10-1SO



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKC 2,5/10-ST-5,08 BD:10-1SO
Catalog number	FKC 2,5/10-ST-5,08 BD:10-1SO
Category	PCB Connectors (PCC)
Minimum order	1000 Product
Document ID	EO-C5D5DBE21F
Generated	2026-08-04

Product Overview

FKC 2,5/10-ST-5,08 BD:10-1SO 1367611 PHOENIX CONTACT Printed circuit board connector, nominal section: 2.5 m..

STRUCTURED PRODUCT DATA

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Type of connection (EF000064)	Other
Contact type (EF001587)	Bus
Number of plug-in contact rows (EF006935)	1
Modular spacing contacts (EF007326)	5.08 mm
Modular spacing connections (EF006827)	5.08 mm
Angle contact/conductor connection (EF007546)	Other
Rated current I _n (EF008250)	12 A
Rated voltage (EF000228)	320 V
Rated surge voltage (EF002993)	4 kV
Over voltage category (EF006785)	III
Pollution degree (EF006786)	2
Connectable conductor cross section fine-strand without cable end sleeve (EF007341)	0.2 mm ²
Connectable conductor cross section fine-strand with cable end sleeve (EF007339)	0.25 mm ²
Connectable conductor cross section solid-core (EF007337)	0.2 mm ²
Type of electric connection (EF003961)	Spring clamp connection

CONTINUED

Technical Specifications

TECHNICAL ATTRIBUTE	VALUE
Connectable cable type (EF006816)	Tubular cable
Material of contact surface (EF004020)	Tin
Material contact (EF007544)	Copper
Material insulation body (EF007543)	Polyamide (PA)
Housing material (EF001596)	Other
Housing colour (EF000136)	Green
Inflammability class of insulation material according to UL94 (EF002521)	V0
Operating temperature (EF002393)	-40 °C

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

ETIM for 1367611 Connectors (EC002638)

Feature Name

Feature Value

Type of connection (EF000064)

Other

Contact type (EF001587)

Bus

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5.08 mm

Modular spacing connections (EF006827)

5.08 mm

Angle contact/conductor connection (EF007546)

Other

Rated current I_n (EF008250)

12 A

Rated voltage (EF000228)

320 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Type of electric connection (EF003961)

Spring clamp connection

Connectable cable type (EF006816)

Tubular cable

Material of contact surface (EF004020)

Tin

Material contact (EF007544)

Copper

Material insulation body (EF007543)

Polyamide (PA)

Housing material (EF001596)

Other

Housing colour (EF000136)

Green

Inflammability class of insulation material according to UL94...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKC 2,5/10-ST-5,08 BD:10-1SO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.