

INDUSTRIAL COMPONENT DATA

SH-8ESS48AH000S 1627204 PHOENIX CONTACT Device connector, rear mounting

Brand: PHOENIX CONTACT | Manufacturer Part Number: SH-8ESS48AH000S



Manufacturer	PHOENIX CONTACT
MPN / Reference	SH-8ESS48AH000S
Catalog number	1627204
Category	Circular connector, mounting (without cable)
Minimum order	1 Pcs
Document ID	EO-9CB8B9789D
Generated	2026-08-06

Product Overview

Device connector, rear mounting

M23, Conect. plug. to be apar. poster wall., SH, straight, shielded: yes, for standard lock and SPEEDCON, No. of poles: 8+4+PE, contact type: Female, Crimped connection, Flat joint, Central fixing M26 x 1, Min. wall thickness: 1.5 mm, Max. wall thickness: 5 mm, coding:N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Field Device Connectors (FDC)**

Additional Product Information

Key Commercial Data

Orderkey 1627204

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 118 (C-2-2017)

GTIN 4055626407999

Weight per Piece (excluding packing) 55.400 g

Custom tariff number 85366990

Country of origin DE (Germany)

Temperature range

Ambient temperature (operation) -40 °C ... 130 °C

Data of the insulating body

Note Order information: Crimp contacts, 8 x Ø 1 mm, 5 x Ø 2 mm, order separately

Coding N

Insulator material PA 6.6

Insertion/withdrawal cycles mechanical 100

Contact connection method Crimp connection

Type of contacts Socket

Application Hybrid

Number of positions 13

Contact diameter of power contacts 2 mm

Litz wire cross section of power contacts min. 0.25 mm²

Litz wire cross section of power contacts max. 4 mm²

Nominal current per power contact at 25°C 30 A

Rated surge voltage 6 kV

Rated voltage (II/3) power contact 850 V DC

Rated voltage (III/3) power contact 630 V₀AC

Contact diameter of signal contacts 1 mm

Litz wire cross section of signal contacts min. 0.06 mm²

Litz wire cross section of signal contacts max. 1 mm²

Nominal current per signal contact at 25°C 8 A

Rated surge voltage 1.5 kV

Rated voltage (III/3) signal contact 50 V

Housing data

Housing material CuZn

Type of locking for standard and SPEEDCON interlock

Degree of protection (when plugged in) IP67

Thread type M23

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SH-8ESS48AH000S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.