

INDUSTRIAL COMPONENT DATA

FKC 2,5/ 4-ST-5,08 BD:L1-N 1705347 PHOENIX CONTACT Plug-in part, rated current: 12 A, sizing voltage (III/2)..

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKC 2,5/ 4-ST-5,08 BD:L1-N



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKC 2,5/ 4-ST-5,08 BD:L1-N
Catalog number	1705347
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-B596F1DAB3
Generated	2026-08-06

Product Overview

Plug-in part, rated current: 12 A, sizing voltage (III/2): 320 V, number of poles: 4, pitch: 5.08 mm, connection type: Push-in spring connection, color: green, contact surface: Tin

Connector for printed circuit board, nominal section: 2.5 mm², color: green, rated current: 12 A, sizing voltage (III/2): 320 V, surface contacts: Tin, contact type: Connection female, Number of potentials: 4, Number of rows: 1, Number of poles per row: 4, number of connections: 4, article family: FKC 2.5/.. -ST, pitch: 5.08 mm, connection type: Push-in spring connection, conductor/printed circuit board connection address: 0°, Stecksystem: CLASSIC COMBICON, Lock: sin, packing type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Plug component, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 4, pitch: 5.08 mm, connection method: Push-in spring connection, color: green, contact surface: Tin

Your advantages

Time saving push-in connection, tools not requiredIntuitive use through colour coded actuation leverQuick and convenient testing using integrated test optionCan be combined with the MSTB 2',5 rangeKey Commercial Data

Orderkey 1705347

Packing unit 1

GTIN 4046356767408

Custom tariff number 85366990

General

Range of articles FKC 2,5/...-ST

Type of contact Female connector

Number of positions 4

Connection method Push-in spring connection

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 320 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Internal cylindrical gage A2

Stripping length 10 mm

Connection data

Conductor cross section solid min. 0.2 mm²Conductor cross section solid max. 2.5 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 2.5 mm²Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conduct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKC 2,5/ 4-ST-5,08 BD:L1-N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.