

INDUSTRIAL COMPONENT DATA

MCV 1,5/ 4-G-3,5 P26 THRR32S 1707820 PHOENIX CONTACT

Base housing, rated current: 8 A, number of poles: 4, p..

Brand: PHOENIX CONTACT | Manufacturer Part Number: MCV 1,5/ 4-G-3,5 P26 THRR32S



Manufacturer	PHOENIX CONTACT
MPN / Reference	MCV 1,5/ 4-G-3,5 P26 THRR32S
Catalog number	1707820
Category	Printed circuit board connector
Minimum order	140 Pcs
Document ID	EO-66DFE56899
Generated	2026-08-06

Product Overview

Base housing, rated current: 8 A, number of poles: 4, pitch: 3.5 mm, color: black, contact surface: Tin, mounting: Solder THR

Base case printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MCV 1.5/.. -G-THR, pitch: 3.5 mm, mounting: Solder THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MC 1.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 32 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Header, nominal current: 8 A, number of positions: 4, pitch: 3.5 mm, color: black, contact surface: Tin, mounting: THR soldering

Your advantages

Designed for integration into the SMT soldering process
 Vertical connection enables multi-row arrangement on the PCB
 Maximum flexibility when it comes to device design - one header for connectors with different connection technologies

Key Commercial Data

Orderkey 1707820

Packing unit 1

GTIN 4046356949019

Custom tariff number 85366930

General

Range of articles MCV 1,5/...-G-THR

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Color black

Number of positions 4

Standards and Regulations

Connection in acc. with standard EN-VDE

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

eCl@ss

eCl@ss 5.1 27260701

eCl@ss 6.0 27260704

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

ETIM

ETIM 5.0 EC002637

ETIM 6.0 EC002637

UNSPSC

UNSPSC 13.2 39121409

ETIM for 1707820 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

4

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

3.5 mm

Modular spacing connections (EF006827)

3.5 mm

Rated current In (EF008250)

8 A

Rated voltage (EF000228)

160 V

Rated surge voltage (EF002993)

2.5 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Material of conta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MCV 1,5/ 4-G-3,5 P26 THRR32S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.