


INDUSTRIAL COMPONENT DATA

FKCOR 2,5/ 8-ST-5,08 1861292 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKCOR 2,5/ 8-ST-5,08



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKCOR 2,5/ 8-ST-5,08
Catalog number	1861292
Category	Cable connector
Minimum order	100 Pcs
Document ID	EO-D53E991D1F
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 8, number of rows: 1, number of poles: 8, number of connections: 8, article family: FKCOR 2.5/.. -ST, pitch: 5.08 mm, connection type: Push-in spring connection, conductor connection direction/printed circuit board: 90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1861292

Packing unit 100 pc

Note Made to Order (non-returnable)

GTIN 4055626125374

Weight per Piece (excluding packing) 10.110 g

Custom tariff number 85366990

Country of origin SK (Slovakia)

Dimensions

Length [l] 23.7 mm

Width [w] 40.51 mm

Height [h] 14.3 mm

Pitch 5.08 mm

Dimension a 35.56 mm

General

Range of articles FKCOR 2,5/..-ST

Number of positions 8

Connection method Push-in spring connection

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 250 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Insulating material PA

Flammability rating according to UL 94 V0

Stripping length 10 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.14 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Standards and Regulations

Connection in acc. with standard EN-VDE

Flammabilit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKCOR 2,5/ 8-ST-5,08 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.