


## INDUSTRIAL COMPONENT DATA

# PT 1,5/ 2-PH-3,5 YE 1807049 PHOENIX CONTACT PCB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/ 2-PH-3,5 YE



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | PHOENIX CONTACT     |
| MPN / Reference | PT 1,5/ 2-PH-3,5 YE |
| Catalog number  | 1807049             |
| Category        | Cable connector     |
| Minimum order   | 250 Pcs             |
| Document ID     | EO-A21F8ED4D5       |
| Generated       | 2026-08-06          |

## Product Overview

PCB connector

Connector for printed circuit board, nominal section: 1.5 mm<sup>2</sup>, color: yellow, nominal current: 8 A, nominal voltage (III/2): 200 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: PT 1.5/..-PH, pitch: 3.5 mm, connection type: Screw connection with wire protection bracket, screw clamping form: L Longitudinal slot, connection direction conductor/printed circuit board: 0 °, plug-in system: COMBICON PST 1.0, lock: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross section: 1.5 mm<sup>2</sup>, color: yellow, nominal current: 8 A, rated voltage (III/2): 200 V, contact surface: Sn, contact connection type: Socket, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 2, product range: PT 1,5/..-PH, pitch: 3.5 mm, connection method: Screw connection with wire protector, screw head form: L Slotted, conductor/PCB connection direction: 0 °, plug-in system: COMBICON PST 1,0, locking: without, mounting: without, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

## Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family PT 1,5/..-PH

Product line COMBICON Connectors S

Number of positions 2

Pitch 3.5 mm

Number of connections 2  
Number of rows 1  
Number of potentials 2  
Mounting flange without  
Data management status  
Article revision 03  
Electrical propertiesNominal current IN 8 A  
Nominal voltage UN 200 V  
Contact resistance 1.4 mΩ  
Rated voltage (III/3) 160 V  
Rated surge voltage (III/3) 2.5 kV  
Rated voltage (III/2) 200 V  
Rated surge voltage (III/2) 2.5 kV  
Rated voltage (II/2) 400 V  
Rated surge voltage (II/2) 2.5 kV  
Connection dataConnection technology  
Type Plug for pin strip  
Connector system COMBICON PST 1,0  
Nominal cross section 1.5 mm²  
Contact connection type Socket  
Interlock  
Locking type without  
Mounting flange without  
Conductor connection  
Connection method Screw connection with wire protector  
Conductor/PCB connection direction 0 °  
Conductor cross section rigid 0.2 mm² ... 1.5 mm²  
Conductor cross section flexible 0.2 mm² ... 1.5 mm²  
Conductor cross section AWG 26 ... 16  
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 0.75 mm²  
2 conductors with same cross section, solid 0.2 mm² ... 0.34 mm²  
2 conductors with same cross section, flexible 0.2 mm² ... 0.5 mm²  
Cylindrical gauge a x b / diameter 2.4 mm x 1.5 mm / 1.9 mm  
Stripping length 5 mm  
Drive form screw head Slotted (L)  
Tightening torque 0.22 Nm ... 0.25 Nm  
Material specificationsMaterial data - contact  
Note WEEE/RoHS-compliant, free of whis...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/ 2-PH-3,5 YE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.