


## INDUSTRIAL COMPONENT DATA

# DFMC 1,5/ 2-ST-3,5 BD:12-11 1716675 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFMC 1,5/ 2-ST-3,5 BD:12-11



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | DFMC 1,5/ 2-ST-3,5 BD:12-11 |
| Catalog number  | 1716675                     |
| Category        | Cable connector             |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-FB032CFF70               |
| Generated       | 2026-08-06                  |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 1.5 mm<sup>2</sup>, color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 2, number of poles: 2, number of connections: 4, family of articles: DFMC 1,5/..-ST, pitch: 3.5mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON DFMC 1.5, lock: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross section: 1.5 mm<sup>2</sup>, color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Socket, number of potentials: 4, number of rows: 2, number of positions: 2, number of connections: 4, product range: DFMC 1,5/..-ST, pitch: 3.5 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0°, plug-in system: COMBICON DFMC 1,5, locking: without, mounting: without, type of packaging: packed in cardboard

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | PHOENIX CONTACT > PCB Connectors (PCC) |
|--------------|----------------------------------------|

### Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family DFMC 1,5/..-ST

Product line COMBICON Connectors S

Number of positions 2

Pitch 3.5 mm

Number of connections 4  
Number of rows 2  
Number of potentials 4  
Data management status  
Article revision 04  
Electrical propertiesNominal current IN 8 A  
Nominal voltage UN 160 V  
Contact resistance 2 mΩ  
Rated voltage (III/3) 160 V  
Rated surge voltage (III/3) 2.5 kV  
Rated voltage (III/2) 160 V  
Rated surge voltage (III/2) 2.5 kV  
Rated voltage (II/2) 320 V  
Rated surge voltage (II/2) 2.5 kV  
Connection dataConnection technology  
Type Plug component  
Connector system COMBICON DFMC 1,5  
Nominal cross section 1.5 mm²  
Contact connection type Socket  
Interlock  
Locking type without  
Mounting flange without  
Conductor connection  
Connection method Push-in spring connection  
Conductor/PCB connection direction 0 °  
Conductor cross section rigid 0.2 mm² ... 1.5 mm²  
Conductor cross section flexible 0.2 mm² ... 1.5 mm²  
Conductor cross section AWG 24 ... 16  
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 1.5 mm²  
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.14 mm² ... 0.75 mm²  
Cylindrical gauge a x b / diameter 2.4 mm x 1.5 mm / 1.6 mm  
Stripping length 10 mm  
Specifications for ferrules without insulating collar  
recommended crimping tool 1212034 CRIMPFOX 6  
ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm²; Length: 7 mm  
Cross section: 0.34 mm²; Length: 7 mm...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFMC 1,5/ 2-ST-3,5 BD:12-11 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.