


INDUSTRIAL COMPONENT DATA

FKCVR 2,5/ 2-ST BK 1800533 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKCVR 2,5/ 2-ST BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKCVR 2,5/ 2-ST BK
Catalog number	1800533
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-9394E0C9B1
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, article family: FKCVR 2.5/.. -ST, pitch: 5 mm, connection type: Push-in spring connection, conductor connection direction/printed circuit board: 90°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1800533

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4017918961749

Weight per Piece (excluding packing) 3.340 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [l] 26.6 mm

Width [w] 10.1 mm

Height [h] 16.8 mm

Pitch 5 mm

Dimension a 5 mm

General

Range of articles FKCVR 2,5/..-ST

Number of positions 2

Connection method Push-in spring connection

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm²

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 1.5 mm²

Minimum AWG according to UL/CUL 26

Maximum AWG according to UL/CUL 12

Standards and Regulations

Connection in acc. with standard EN-VDE

CUL

Environmental Product Compliance...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKCVR 2,5/ 2-ST BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.