

INDUSTRIAL COMPONENT DATA

FKCVW 2,5/ 2-ST GY7035 1700380 PHOENIX CONTACT Cable connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKCVW 2,5/ 2-ST GY7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKCVW 2,5/ 2-ST GY7035
Catalog number	1700380
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-113CAEB543
Generated	2026-08-06

Product Overview

Cable connector

Connector for printed circuit board, nominal section: 2.5 mm², color: bright gray, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, type of contact: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: FKCVW 2,5/..-ST, pitch: 5 mm, connection type: Push-in spring connection, conductor connection direction/printed circuit board: -90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2,5, locking: without, fixing type: without, packaging type: boxed

PCB connector, nominal cross section: 2.5 mm², color: light gray, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Socket, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 2, product range: FKCVW 2,5/..-ST, pitch: 5 mm, connection method: Push-in spring connection, conductor/PCB connection direction: -90 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family FKCVW 2,5/..-ST

Product line COMBICON Connectors M

Number of positions 2

Pitch 5 mm

Number of connections 2
Number of rows 1
Number of potentials 2
Mounting flange without
Data management status
Article revision 03
Electrical propertiesNominal current IN 12 A
Nominal voltage UN 320 V
Contact resistance 1 m?
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
Connection dataConnection technology
Type Standard
Connector system COMBICON MSTB 2,5
Nominal cross section 2.5 mm²
Contact connection type Socket
Interlock
Locking type without
Mounting flange without
Conductor connection
Connection method Push-in spring connection
Conductor/PCB connection direction -90 °
Conductor cross section rigid 0.2 mm² ... 2.5 mm²
Conductor cross section flexible 0.2 mm² ... 2.5 mm²
Conductor cross section AWG 24 ... 12
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 2.5 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 2.5 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.5 mm² ... 1.5 mm²
Cylindrical gauge a x b / diameter 2.8 mm x 2.0 mm / 2.0 mm
Stripping length 10 mm
Specifications for ferrules without insulating collar
recommended crimping tool 1212034 CRIMPFOX 6
Specification...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKCVW 2,5/ 2-ST GY7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.