

INDUSTRIAL COMPONENT DATA

FKDSO 2,5/ 4-L GY LCBK 1064464 PHOENIX CONTACT PCB terminal block FKDSO 2,5/ 4-L GY LCBK 1064464

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKDSO 2,5/ 4-L GY LCBK



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKDSO 2,5/ 4-L GY LCBK
Catalog number	1064464
Category	Printed circuit board terminal
Minimum order	250 Pcs
Document ID	EO-C4AD85F2DA
Generated	2026-08-05

Product Overview

PCB terminal block - FKDSO 2,5/ 4-L GY LCBK - 1064464

Terminal block for printed circuit board, nominal current: 22 A, nominal voltage (III/2): 250 V, nominal section: 2.5 mm², number of potentials: 4, number of rows: 1, number of poles per row: 4, family of articles: FKDSO 2.5/.. -L, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: gray, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1. Item with side pin output on the left

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

PCB terminal block

Key Commercial Data

Orderkey 1064464

Packing unit 1

GTIN 4055626720289

Custom tariff number 85369010

Product type Printed circuit board terminal

Approval EAC

cULus Recognized

Classifications

eCI@ss

eCI@ss 5.1 27261100

eCI@ss 6.0 27261100

eCI@ss 7.0 27440401

eCI@ss 8.0 27440401

eCI@ss 9.0 27440401

ETIM

ETIM 5.0 EC002643

ETIM 6.0 EC002643

ETIM 7.0 EC002643

ETIM for 1064464 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

19.05 mm

Number of electrical connections (EF008252)

4

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5 mm

Rated current In (EF008250)

22 A

Rated voltage (EF000228)

250 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Spring clamp connection

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm²

Connectable conductor cross section multi-wired (EF007343)

2.5 mm²

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.4 mm

Length pin (EF006825)

3.5 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Grey

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of PCB....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKDSO 2,5/ 4-L GY LCBK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.