

INDUSTRIAL COMPONENT DATA

FKDSO 2,5/ 4-R1 6018 1856472 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKDSO 2,5/ 4-R1 6018



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKDSO 2,5/ 4-R1 6018
Catalog number	1856472
Category	Printed circuit board terminal
Minimum order	200 Pcs
Document ID	EO-656FAB6A64
Generated	2026-08-06

Product Overview

PCB terminal block

Terminal block for printed circuit board, nominal current: 20 A, nominal voltage (III/2): 320 V, nominal section: 2.5 mm², number of potentials: 1, number of rows: 1, number of poles per row: 1, family of articles: FKDSO 2.5/ .. R1, pitch: 5mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/PCB connection direction: 0°, color: yellowish-green, number of solder pins per potential: 1, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1856472

Packing unit 1

GTIN 4055626120010

Custom tariff number 85369010

Dimensions

Pitch 5 mm

Hole diameter 1.4 mm

General

Range of articles FKDSO 2,5/ ..R1

Insulating material group I

Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 200 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 20 A
Nominal cross section 2.5 mm²
Contact material Cu alloy
Solder pin surface
Flammability rating according to UL 94 V0
Stripping length 10 mm
Number of positions 1
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 4 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 1 mm²
Standards and Regulations
Connection in acc. with standard EN-VDE
Flammability rating according....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKDSO 2,5/ 4-R1 6018 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.